#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization

International Bureau



## 

### (43) International Publication Date 25 March 2004 (25.03.2004)

## (10) International Publication Number WO 2004/024452 A2

(51) International Patent Classification7:

**B41J** 

(21) International Application Number:

PCT/US2003/027145

(22) International Filing Date: 27 August 2003 (27.08.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/410,607

13 September 2002 (13.09.2002) US

(71) Applicants (for all designated States except US): TOSOH SMD, INC. [US/US]; 3600 Gantz Road, Grove City, OH 43123 (US). HEWLETT-PACKARD CO. [US/US]; 1000 NE Circle Boulevard, Corvalis, OR 97330-4239 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SMATHERS, David, B. [US/US]; 3298 Kirkham Road, Columbus, OH 43123 (US). VALENT, Francis, S. [US/US]; 6023 Epernay Way, Galloway, OH 43119 (US). REGAN, Michael, J. [US/US]; 3210 NW Arrowood Circle, Corvallis, OR 97330 (US).


- (74) Agent: PEACOCK, Bruce, E.; Wegman, Hessler & Vanderburg, 6055 Rockside Woods Boulevard, Suite 200, Cleveland, OH 44131 (US).
- (81) Designated States (national): JP, US.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

#### Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR MAKING DENSE MIXED METAL Si<sub>3</sub>N<sub>4</sub> TARGETS



(57) Abstract: A composition and method for fabricating high-density Ta-Al-O, Ta-Si-N, and W-Si-N sputtering targets, having particular usefulness for the sputtering of heater layers for ink jet printers. Compositions in accordance with the invention comprise a metal component, Si<sub>3</sub>N<sub>4</sub>, and a sintering aid so that the targets will successfully sputter without cracking, etc. The components are combined in powder form and pressure consolidated under heated conditions for a time sufficient to form a consolidated blend having an actual density of greater that about 95% of the theoretical density. The consolidated blend may then be machined so as to provide the final desired target shape.

